




LISTA DE RENDIMIENTOS DE ELECTROBOMBAS SUMERGIBLES PARA PERFORACION Ø 6" (150 MM)

Ejecución totalmente en acero inoxidable

ALTURA MANOMETRICA TOTAL (metros)

Mod.	HP	DN	ALTURA MANOMETRICA TOTAL (metros)																														Hmax m							
			0	5	10	15	20	25	30	35	40	45	50	60	70	80	90	100	110	120	130	140	150	160	170	180	190	200	210	220	230	240		250	260	270	280	290	300	
S6P17-13	10	3"													20,2	18,8	17,2	16,1	13,5	11,2	3																		145	
S6P17-20	15	3"																	20,6	19,5	18,8	17,6	16,7	15,7	13,8	12	7,5	0										210		
S6P17-27	20	3"																				21	20,4	19,8	19,2	18,7	18	17,1	15,8	14,4	13,5	12,6	11,3	10	7,5	4,5		298		
S6P30-3	4	3"				36	33	27	18	0																													34	
S6P30-6	7,5	3"									35	33	31	27	17	0																							69	
S6P30-8	10	3"												34,5	31,1	25,2	16,5	0																					90	
S6P30-13	15	3"													36	34,8	33,7	30	25,8	21,8	16,5	9	0																150	
S6P30-17	20	3"																35,4	33,6	32,1	30	27,6	24	21	16,5	12	6											198		
S6P46-3	7,5	3"				57	48	39	21	0																													40	
S6P46-5	10	3"						58,5	54	49,5	45	40,2	24																										68	
S6P46-7	15	3"							58,5	55	52,5	43,2	37,5	27	12																								94	
S6P46-10	20	3"									60	57	52,5	48,9	43,5	37,5	30	21	9																				135	
S6P46-12	25	3"										60	57,6	54	51	46,5	42	36,9	30,9	24	15	3																		161
S6P60-3	7,5	3"		78	73	68,5	55	42,4	30	15																													43	
S6P60-4	10	3"			71,3	65	57,8	50	41,3	32	21,3																												56	
S6P60-6	15	3"					71,3	68	63,7	60	55	43,7	31,2	15																									85	
S6P60-8	20	3"					78	75	71,3	69	66,5	61,3	51,6	43,7	33,7	25	10,8																						114	
S6P60-9	25	3"							77,4	75	71,3	66,5	61,3	51,5	45	36,2	27	18																					126	
S6P60-12	30	3"									78	73	70,3	66,5	61,3	55,5	50	43,7	37,5	31,3	25,5	16,2	3,8																172	
S6P60-17	40	3"										78	77,4	76,2	70,8	68,8	65	61,3	56	52,5	48,2	43,7	40	36,2	31,3	27	21,3	15										243		
S6CR90K 20/5	20	4"					120	113	105	93	82	75	50	0																									70	
S6CR90K 25/6	25	4"						120	113	106	97	90	75	55	25																								84	
S6CR90K 30/7	30	4"							120	114	108	102	88	73	55	32	0																						98	
S6CR90K 40/10	40	4"										120	112	104	95	85	74	62	48	30	0																		140	

Caudal en m3/h



Sylwan S.A. | Av. Juan Domingo Peron 7669
 S2010ACA - Rosario - Santa Fe - Argentina
 Tel.: +54 (341) 456 5020 / 458 0050 / 457 0044 / 459 3540
 Fax: +54 (341) 456 9723
 bombas@sylwan.com.ar | www.sylwan.com.ar