

BOMBA TURBINA PARA POZO PROFUNDO



Sylwan

MODELO P 300 PS

PERFORACION : MINIMO ϕ INTERIOR 12" (305 mm)

1460 R.P.M.

CANTIDAD CUERPOS	1		2		3		4		5		6		7		8	
	m3/h	m	HP	m	HP	m	HP	m	HP	m	HP	m	HP	m	HP	
300	11,5	17,0	23,0	34,0	34,5	51,0	46,0	68,0	57,5	85,0	69,0	102,0	80,5	119,0	92,0	136,0
350	11,5	19,0	23,0	38,0	34,5	57,0	46,0	76,0	57,5	95,0	69,0	114,0	80,5	133,0	92,0	152,0
400	11,5	21,0	23,0	42,0	34,5	63,0	46,0	84,0	57,5	105,0	69,0	126,0	80,5	147,0	92,0	168,0
450	10,0	22,0	20,0	44,0	30,0	66,0	40,0	88,0	50,0	110,0	60,0	132,0	70,0	154,0	80,0	176,0
500	8,6	23,0	17,2	46,0	25,8	69,0	34,4	92,0	43,0	115,0	51,6	138,0	60,2	161,0	68,8	184,0
550	7,8	22,0	15,6	44,0	23,4	66,0	31,2	88,0	39,0	110,0	46,8	132,0	54,6	154,0	62,4	176,0

1760 R.P.M.

CANTIDAD CUERPOS	1		2		3		4		5		6					
	m3/h	m	HP	m	HP	m	HP	m	HP	m	HP	m	HP			
300	17,7	31,0	35,4	62,0	53,1	93,0	70,8	124,0	88,5	155,0	106,2	186,0				
350	17,0	32,0	34,0	64,0	51,0	96,0	68,0	128,0	85,0	160,0	102,0	192,0				
400	16,2	34,0	32,4	68,0	48,6	102,0	64,8	136,0	81,0	170,0	97,2	204,0				
450	16,0	35,0	32,0	70,0	48,0	105,0	64,0	140,0	80,0	175,0	96,0	210,0				
500	15,8	37,0	31,6	74,0	47,4	111,0	63,2	148,0	79,0	185,0	94,8	222,0				
550	14,8	38,0	29,6	76,0	44,4	114,0	59,2	152,0	74,0	190,0	88,8	228,0				
600	13,0	39,0	26,0	78,0	39,0	117,0	52,0	156,0	65,0	195,0	78,0	234,0				
650	11,7	40,0	23,4	80,0	35,1	120,0	46,8	160,0	58,5	200,0	70,2	240,0				

m = Metros manométricos (presión en la descarga del cuerpo de la bomba)

H.P. = Potencia absorbida en el eje del cuerpo de la bomba